

35 Ton Detachable Gooseneck Lowboy - Ground Bearing

Capacity: 70,000#

Trailer weight: 15,300# (approx)

Gross vehicle weight rating: 85,300#

Dimensions:

Length: 44' 10"

Width: 8' 6" w/12" outriggers (8' also available)

Loadwell length: 22'

Loadwell height: 25" unloaded

Gooseneck style & dimensions:

Style: 2 angle scraper

Length: 11' 6"

5th wheel height: 50"

Swing clearance: 90"

Kingpin; Size 2" - Setting: 15"

Hydraulic system:

Engine: 10 HP Briggs & Stratton, electric start

Pump: Mckers V-10, 2 GPM @ 1200RPM

Control valve: Bucher HDM 140

Cylinder: 6" bore w/22" stroke

Bed structure w/tapered front beam:

Main frame: W16x57 beams A572 grade 50, HI-TENSILE with tapered front beam

Side channel: C12x20.7

Cross members: W8x10, full width

Decking: 2" Oak on load sides

Outriggers: Cast 12" - 12 per side

Suspension:

Hutch 9700, 4 spring

Axes:

2 each 5" round 25,000# capacity, 10 stud unimount or 5 spoke wheels

Rims & tires:

Hub piloted or Dayton style 8:25 x 22.5

12 - 255/70 R 22.5 LRH

Brake system:

ABS required in U.S. & Canada

16 1/2" x 7" air S cam w/automatic slack adjusters

Type 30/30 brake chambers

Light system:

Sealed modular wire harness

12-volt rubber mounted seal beam lights

Reflective tape

Lashing "D" rings:

3 per side of deck

1 on trunion between tires

Finish: Acrylic high gloss enamel

Colors - Red, Dark Blue, Black, New Cat Yellow, Dark Green, Orange, Gray

OPTIONS:

**Additional neck & deck lengths **Other widths 9' & 10' **Air ride & single point suspensions

**Front flip ramps **Other size tires **15" axles w/12 1/4" x 7 1/2" brake

**Neck fenders **Lockable storage, neck, bed **Wet line &/or combination

**Bucket wellor tailhydraulic system

**Additional "D" rings **Side channel reinforcement **Special decking

**Beaver tail **Rear fenders **Ramps - 24" x 60" Manual

**Drop side or rail beds 36" x 84" hydraulic

www.LaPineTrucks.com
440-526-6363