

# 35 Ton Detachable Gooseneck Lowboy NON GROUND BEARING

Capacity: 70,000#

Trailer weight: 16,400# (approx)

Gross vehicle weight rating: 86,400#

Dimensions:

Length: 43' 6"

Width: 8' 6" w/12" outriggers (8' also available)

Loadwell length: 22'

Loadwell height: 25" unloaded

Gooseneck style & dimensions:

Style: 2-angle non-ground bearing

Length: 11'

5th wheel height: 50"

Swing clearance: 90"

Kingpin: Size: 2" - Setting 15"

Locking system: Air activated pin

Neck support: Hydraulic

Hydraulic system:

Engine: 10 HP Briggs & Stratton, electric start

Pump: Vickers V-10, 2 GPM @ 1200RPM

Control valve: Bucher HDM11P/2 dual spool

Cylinders:

Neck function 2 - 6" bore w/22" stroke

Neck support 2 1/2" x 12"

Bed structure:

Main frame: W16x57 beams A572 grade 50, HI-TENSILE, with tapered front beam

I - Beam 12X22

Cross members: W8x10, full width

Decking: 2" Oak on load sides

Outriggers: Cast 12" - 12 per side

Suspension: Hutch 9700, 4 spring

Axles: 2 Hendrickson 5" round 25,000# capacity, 10 stud unimount or 5 spoke wheels

Rims & tires:

Hub piloted or Dayton style 8.25 x 22.5

8 - 255/70 R 22.5 LRH

Brake system:

ABS required in U.S. & Canada

16 1/2" x 7" air S cam w/automatic slack adjusters

Type 30/30 brake chambers

Light system:

Sealed modular wire harness

12-volt rubber mounted seal beam lights

Reflective tape

Lashing "D" rings:

3 per side of deck

1 on trunion between tires

Finish: Acrylic high gloss enamel

Colors: Red, Dark Blue, Black, New Cat Yellow, Dark Green, Orange, Gray

OPTIONS:

\*\*Additional neck & deck lengths\*\*Other widths 9' & 10' \*\*Air ride & single point suspensions

\*\*Front flip ramps\*\*Other size tires \*\*15" axles w/12 1/4" x 7 1/2" brake

\*\*Neck fenders\*\*Lockable storage, bed or tail \*\*Wet line &/or combination

\*\*Bucket well\*\*Side channel reinforcement hydraulic system

\*\*Additional "D" rings\*\*Rear fenders \*\*Special decking

\*\*Beaver tail\*\*Ramps - 24" x 60" Manual

\*\*Drop side or rail beds 36" x 84" Hydraulic

**www.LaPineTrucks.com**  
**440-526-6363**