

35 Ton Detachable Gooseneck, Ground bearing - with 36' beaver tail

Capacity: 70,000#
Trailer weight: 15,900# (approx)
Gross vehicle weight rating: 88,300#
Dimensions:

Length: 44' 10"
Width: 8' 6" w/12" outriggers (8' also available)
Loadwell length: 22'
Loadwell height: 25" unloaded
36" beaver tail

Gooseneck style & dimensions:

Style: 2 angle scraper
Length: 11' 6"
5th wheel height: 50"
Swing clearance: 90"
Kingpin: Size 2" - Setting: 15"

Hydraulic system:

Engine: 10 HP Briggs & Stratton, electric start
Pump: Vickers V-10, 2 GPM @ 1200RPM
Control valve: Bucher HDM 140
Cylinder: 6" bore w/22" stroke

Bed structure w/tapered front beam:

Main frame: W16x57 beams A572 grade 50, HI-TENSILE with tapered front beam
I - Beam 12X22

Cross members: W8x10, full width

Decking: 2" Oak on load sides

Outriggers: Cast 12" - 12 per side

Suspension:

Hutch 9700, 4 spring

Axes: 2 each Hendrickson 5" round 25,000# capacity, 10 stud unimount or 5 spoke wheels

Rims & tires:

Hub: piloted or Dayton style 8:25 x 22.5
8 - 255/70 R 22.5 LRH

Brake system:

ABS required in U.S. & Canada
16 1/2" x 7" air S cam w/automatic slack adjusters
Type 30/30 brake chambers

Light system:

Sealed modular wire harness
12-volt rubber mounted seal beam lights
Reflective tape

Lashing "D" rings:

3 per side of deck
1 on trunion between tires

Finish: Acrylic high gloss enamel

Colors - Red, Dark Blue, Black, New Cat Yellow, Dark Green, Orange, Gray

OPTIONS:

Additional neck & deck lengthsOther widths 9' & 10' **Air ride & single point suspensions

Front flip rampsOther size tires **15" axles w/12 1/4" x 7 1/2" brake

Neck fendersLockable storage, neck, bed **Wet line &/or combination

**Bucket wellor tail hydraulic system

Additional "D" ringsSide channel reinforcement**Special decking

Beaver tailRear fenders **Ramps - 24" x 60" Manual

**Drop side or rail beds 36" x 84" hydraulic



www.LaPineTrucks.com
440-526-6363