

40 Ton Detachable Gooseneck Lowboy - GROUND BEARING

Capacity: 80,000#

Trailer weight: 17,300# (approx)

Gross vehicle weight rating: 87,300#

Dimensions:

Length: 45'

Width: 8' 6" w/12" outriggers (8' also available)

Loadwell length: 22'

Loadwell height: 25" unloaded

Gooseneck style & dimensions:

Style: 2-angle scraper

Length: 11' 6"

5th wheel height: 50"

Swing clearance: 90"

Kingpin: Size: 2" - Setting 15"

Hydraulic system:

Engine: 10 HP Briggs & Stratton, electric start

Pump: Vickers V-10, 2 GPM @ 1200RPM

Control valve: Bucher HDM 140

Cylinder: 1 - 8" bore w/22" stroke

Bed structure:

Main frame: W16x77 beams A572 grade 50, HI-TENSILE, with tapered front beam

I-Beam 12X22

Cross members: W8x10, full width

Decking: 2" Oak on load sides

Outriggers: Cast 12" - 12 per side

Suspension: Hutch 9700, 4 spring

Axles: 2 Hendrickson 5" round 25,000# capacity, 10 stud unimount

Rims & tires:

Hub piloted style 8.25 x 22.5

12 - 255/70 R 22.5 LRH

Brake system:

ABS - 2S/1M

16 1/2" x 7" air S cam w/automatic slack adjusters

Type 30/30 brake chambers

Light system:

Sealed modular wire harness

12-volt rubber mounted seal beam lights

Reflective tape

Lashing "D" rings:

3 per side of deck

1 on trunion between tires

Finish: Acrylic high gloss enamel

Colors: Red, Dark Blue, Black, New Cat Yellow, Dark Green, Orange, Gray

OPTIONS:

Additional neck & deck lengthsOther widths 9' & 10' **Front flip ramps

Air ride & walking beam **Other size tires15" axles w/ 12 1/4" x 7 1/2" brake

suspensions**Lockable storage neck, **Wet line &/or combination

**Bucket wellbed or tailhydraulic system

Rear fendersSide channel reinforcement

Additional "D" ringsAdditional "D" rings**Special decking

Lift or flip axlesBeaver tail**Ramps - 36" x 84" Hydraulic

**Drop side or rail beds

www.LaPineTrucks.com
440-526-6363