

Model: RG-50 Detachable Gooseneck - GROUND BEARING

Capacity: 100,000# (45359kg)
Trailer weight: 20,300# (9207kg) (approx)
Gross vehicle weight rating: 120,300# (54567kg)

Dimensions:

Length: 48' 10" (14884.6mm)
Width: 8' 6" (2590.8mm) w/12" (304.8mm) outriggers (8' also available)
Loadwell length: 22' (6705.6mm)
Loadwell height: 25" (628.8mm) unloaded

Gooseneck style & dimensions:

Style: 2-angle scraper
Length: 11' 6" (3505.2mm)
5th wheel height: 50" (1270.1mm)
Swing clearance: 90" (2286mm)
Kingpin: Size: 2" (50.9mm) - Setting 15" (381mm)

Hydraulic system:

Engine: 10 HP Briggs & Stratton, electric start
Pump: Vickers V-10, 2 GPM @ 1200RPM
Control valve: Prince 2500
Cylinder: 1 - 8" bore w/22" stroke

Bed structure:

Main frame: W16x77 beams A572 grade 50, HI-TENSILE, with tapered front beam
I-Beam 12X22
Cross members: W8x10, full width
Decking: 2" Oak on load sides
Outriggers: Cast 12" - 12 per side

Suspension: Hutch 9700, 6 spring

Axes: 3 Hendrickson 5" round 25,000# (11339kg) capacity, 10 stud unimount or 5 spoke wheels

Rims & tires:

Hub piloted or Dayton style 8.25 x 22.5
12 -11 R 22.5 LRG

Brake system:

16 1/2" x 7" air S cam w/automatic slack adjusters
Type 30 & 30/30 brake chambers

Light system:

Sealed modular wire harness
12-volt rubber mounted seal beam lights
Reflective tape

Lashing "D" rings:

3 per side of deck
1 on trunion between tires

Finish: Acrylic high gloss enamel

Colors: Red, Dark Blue, Black, New Cat Yellow, Dark Green, Orange, Gray

OPTIONS:

Additional neck & deck lengthsOther widths 9' & 10' **Front flip ramps
Air ride & walking beam **Other size tires15" axes w/1 1/2" x 7 1/2" brake
suspensions**Lockable storage neck, **Wet line &/or combination
**Bucket wellbed or tailhydraulic system
Rear fendersSide channel reinforcement
Additional "D" ringsAdditional "D" rings**Special decking
Lift or flip axesBeaver tail**Ramps - 36" x 84" Hydraulic
**Drop side or rail beds



www.LaPineTrucks.com

440-526-6363