

# Model: RG-50 Detachable Gooseneck - GROUND BEARING

Capacity: 100,000# (45359kg)

Trailer weight: 20,300# (9207kg) (approx)

Gross vehicle weight rating: 120,300# (54567kg)

## Dimensions:

Length: 48' 4" (14732mm)

Width: 10' (3048mm) w/12" (304.8mm) outriggersLoadwell length: 22' (6705.6mm)

Loadwell height: 25" (628.8mm) unloaded

## Gooseneck style & dimensions:

Style: 2-angle scraper

Length: 11' 4" (3454mm)

5th wheel height: 50" (1270.1mm)

Swing clearance: 90" (2286mm)

Kingpin: Size: 2" (50.9mm) - Setting 15" (381mm)

## Hydraulic system:

Engine: 10 HP Briggs & Stratton, electric start

Pump: Vickers V-10, 2 GPM @ 1200RPM

Control valve: Prince 2500

Cylinder: 1 - 8" bore w/22" stroke

## Bed structure:

Main frame: W16x77 beams A572 grade 50, HI-TENSILE, with tapered front beam

1 - Beam 12X22

Cross members: W8x10, full width

Decking: 2" Oak on load sides

Outriggers: Cast 12" - 12 per side

Suspension: Hutch 9700, 6 spring

Axles: 3 Hendrickson 5" round 25,000# (11339kg) capacity, 10 stud unimount or 5 spoke wheels

## Rims & tires:

Hub piloted or Dayton style 8.25 x 22.5

12 -11 R 22.5 LRG

## Brake system:

16 1/2" x 7" air S cam w/automatic slack adjusters

Type 30 & 30/30 brake chambers

## Light system:

Sealed modular wire harness

12-volt rubber mounted seal beam lights

Reflective tape

## Lashing "D" rings:

3 per side of deck

1 on trunion between tires

Finish: Acrylic high gloss enamel

Colors: Red, Dark Blue, Black, New Cat Yellow, Dark Green, Orange, Gray

## OPTIONS:

\*\*Additional neck & deck lengths\*\*Other widths 9' & 10' \*\*Front flip ramps

\*\*Air ride & walking beam \*\*Other size tires\*\*15" axles w/ 12 1/4" x 7 1/2" brake suspensions\*\*Lockable storage neck, \*\*Wet line &/or combination

\*\*Bucket wellbed or tailhydraulic system

\*\*Rear fenders\*\*Side channel reinforcement

\*\*Additional "D" rings\*\*Additional "D" rings\*\*Special decking

\*\*Lift or flip axles\*\*Beaver tail\*\*Ramps - 36" x 84" Hydraulic



[www.LaPineTrucks.com](http://www.LaPineTrucks.com)

440-526-6363