

RG-50 Detachable Gooseneck - GROUND BEARING Rail/Beam Bed

Capacity: 100,000#
Trailer weight: 19,700# (approx)
Gross vehicle weight rating: 119,700#
Dimensions:

Length: 48' 10"
Width: Bed 51" - Axles 8' 6"
Loadwell length: 22'
Loadwell height: 25" unloaded

Gooseneck style & dimensions:

Style: 2-angle scraper
Length: 11' 6"
5th wheel height: 50"
Swing clearance: 90"
Kingpin: Size: 2" - Setting 15"

Hydraulic system:

Engine: 10 HP Briggs & Stratton, electric start
Pump: Vickers V-10, 2 GPM @ 1200RPM
Control valve: Prince 2500
Cylinder: 1 - 8" bore w/22" stroke

Bed structure:

Main frame: W16x77 beams A572 grade 50, HI-TENSILE, with tapered front beam
Beam spreaders
I - Beam 12X22

Suspension: Hutch 9700, 6 spring

Axles: 3 Hendrickson 5" round 25,000# capacity, 10 stud unimount

Rims & tires:

Hub piloted, 10 stud
12 - 255/70 R 22.5 LRH

Brake system:

16 1/2" x 7" air S cam w/automatic slack adjusters
Type 30 & 30/30 brake chambers

Light system:

Sealed modular wire harness
12-volt rubber mounted seal beam lights
Reflective tape

Lashing "D" rings:

3 per side of deck
1 on trunion between tires

Finish: Acrylic high gloss enamel

Colors: Red, Dark Blue, Black, New Cat Yellow, Dark Green, Orange, Gray

OPTIONS:

Additional neck & deck lengthsOther widths 9' & 10' **Front flip ramps

Air ride & walking beamOther size tires**15" axles w/12 1/4" x 7 1/2" brake suspensions**Lockable storage neck, **Wet line &/or combination

**Bucket wellbed or tail hydraulic system

Rear fendersSide channel reinforcement

Additional "D" ringsAdditional "D" rings**Special decking

Lift or flip axlesBeaver tail**Ramps - 36" x 84" Hydraulic

**Drop side or roll beds

www.LaPineTrucks.com
440-526-6363